

**DESCRIPTION 规格**

Total thickness 总厚度	EN ISO 24346	mm	2.5
Thickness of the wearlayer 耐磨层厚度	EN ISO 24340	mm	0.55
Weight 重量	EN ISO 23997	kg/m <sup>2</sup>	4.1
Plank size 片材尺寸	EN ISO 24342	cm	45.7x91.4 / 61x61 / 18.4x121.9 15.2x91.4 / 45.7x45.7 /

**CLASSIFICATION 类别**

Norm / Product specification 产品规范	-	-	ISO 19322
Fire rating 防火等级	IMO认证	-	MSC 307(88) Part 5
			MSC 307(88) Part 2
	海事认证	-	MED
			US Coast Guard
			Transport Canada
			SOLAS 74
Static electrical propensity 抗静电性	EN 1815	KV	<2

**PERFORMANCE 性能**

Wet slip resistance 防湿滑性	DIN 51130	class	R10
Abrasion resistance 耐磨性	EN 660.2	mm <sup>3</sup>	≤2.0
Abrasion group 耐磨等级	EN 649	group	T
Dimensional stability 尺寸稳定性	EN ISO 23999	%	≤ 0.15
Residual indentation 残余凹陷性	EN ISO 24343-1	mm	≤ 0.1
Thermal conductivity 热传导性	EN ISO 10456	W/(m.K)	0.25
Colour fastness 颜色稳定性	EN 20 105 - B02	degree	≥ 6
Chemical products resistance 抗化学性	EN ISO 26987	-	OK
Speical treatment 特殊维护处理	-	-	PUR
TVOC after 28 days 28天后TVOC*排放量	ISO 16000 - 6	µg/m <sup>3</sup>	<10

