

DESCRIPTION 规格

Total thickness 总厚度	EN ISO 24346 (EN 428)	mm	2
Weight 重量	EN ISO 23997 (EN 430)	g/m ²	2850
Width / Length of sheet 卷材宽度/长度	EN ISO 24341 (EN 426)	cm/lm	200/20
Tile Size 块材尺寸	EN ISO24342 (EN427)	mm	608*608

CLASSIFICATION 类别

Norm / Product specification 产品规范	-	-	ENISO 10581 (EN 649)
Fire rating 防火等级	IMO认证	-	MSC 307(88) Part 5
			MSC 307(88) Part 2
	海事认证	-	MED
			US Coast Guard
			Transport Canada
SOLAS 74			
Static electrical propensity 抗静电性	EN 1815	KV	<2

PERFORMANCE 性能

Wet slip resistance 防湿滑性	DIN 51130	class	R9
Type binder content 粘合物分级	ISO 10581	type	I
Dimensional stability 尺寸稳定性	EN ISO 23999 (EN 434)	%	卷材 ≤ 0.4 块材 ≤ 0.25
Residual indentation 残余凹陷性	EN ISO 24343-1 (EN 433)	mm	≤ 0.03
Thermal conductivity 热传导性	EN ISO 10456 (EN 12524)	W/(m.K)	0.25
Colour fastness 颜色稳定性	EN 20105 - B02	degree	≥ 6
Chemical products resistance 抗化学性	EN ISO 26987 (EN 423)	-	OK
Anti-bacterial and fungicidal 抗菌防霉性能	-	-	OK
Surface treatment 特殊维护处理	-	-	Evercare™
TOVC after 28 days 28天后的TVOC*排放量	ISO16000-6	μg/m ³	<10

